

Please amend the claims as follows:

1. (currently amended) ~~Face~~ A face wall (1) for a motor vehicle (2), the face wall having a first wall (3a) and a second wall (3b) at a spacing from ~~same~~, ~~characterised in that the first wall wherein~~ the first wall has a recess (4) to accommodate a brake booster (5) which is fastened solely to the first wall.

2. (currently amended) ~~Face~~ A face wall according to claim 1, ~~characterised in that wherein~~ an edge region (6) of the recess (4) is reinforced.

3. (currently amended) ~~Face~~ A face wall according to claim 2, ~~characterised in that wherein~~ the brake booster (5) has an edge surface (7) which rests on ~~an~~ the edge region (6) of the recess (4).

4. (currently amended) ~~Face~~ A face wall according to claim 3, ~~characterised in that wherein~~ an elastomer ring (8) is arranged on the edge surface (7) of the brake booster (5) on the side oriented towards the edge region (6).

5. (currently amended) ~~Face~~ A face wall according to ~~one of the preceding claims, characterised in that~~ claim 1 wherein the brake booster (5) is screwed to the first wall (3a).

6. (currently amended) ~~Face~~ A face wall according to ~~one of the preceding claims, characterised in that~~ claim 1 wherein the second wall (3b) has a feed-through aperture (10) for the brake booster (5).

7. (currently amended) ~~Face~~ A face wall according to claim 6, ~~characterised in that wherein~~ the gap (11) between the feed-through aperture (10) and brake booster (5) is between 1 mm and 20 mm, ~~preferably between 1 mm and 5 mm~~, in the region of the feed-through aperture.

8. (currently amended) ~~Face~~ A face wall according to ~~one of claims claim 6 or 7, characterised in that~~ wherein the face wall (1) has curvatures in the region of at least one of the recess (4) and ~~for~~ the feed-through aperture (10).

9. (currently amended) ~~Face~~ A face wall according to ~~one of the preceding claims, characterised in that~~ claim 1 wherein the face wall (1) has reinforcing webs in the region of the recess (4).

10. (currently amended) ~~Face~~ A face wall according to ~~one of the preceding claims, characterised in that~~ claim 1 wherein foam (12) is arranged between the first wall (3a) and the second wall (3b).

11. (currently amended) ~~Face A face~~ wall according to ~~one of the preceding claims, characterised in that~~ claim 1 wherein the brake booster is covered on its outer surface (13) with a foam-repelling material.

12. (currently amended) ~~Face A face~~ wall according to ~~one of the preceding claims, characterised in that~~ claim 1 wherein the face wall (1) is designed as a module for mounting in a face wall frame (14) of the body of a motor vehicle.

13. (currently amended) ~~Face A face~~ wall according to ~~one of the preceding claims, characterised in that~~ claim 1 wherein at least one of the first wall (3a) and ~~/or the second wall (3b) are/~~ is formed from one of plastics material ~~or~~ and metal.

14. (currently amended) ~~Motor A motor~~ vehicle (2) containing a face wall according to ~~one of the preceding claims~~ claim 1.